



### Technical data and Specification

- Rated voltage: 500V/660V AC
- Rated breaking capacity: 100KA
- Class: gG-gL
- Standard: IEC/EN 60269-2-1, NFC 63210, UNE 21.103
- Fuse link with indicator or striker are available as requested

Item	In(A)	Packing(pcs)
8.5 X 31.5	2A, 4A, 6A, 10A, 16A, 20A	10/2000
10 X 38	2A, 4A, 6A, 10A, 16A, 20A, 25A, 32A	10/2000
14 X 51	2A, 4A, 6A, 10A, 16A, 20A, 25A, 32A, 40A, 50A, 63A	10/500
22 X 58	10A, 16A, 20A, 25A, 32A, 40A, 50A, 63A, 80A, 100A, 125A	5/300

# Cylindrical Protection Fuse Holder



### Technical data and Specification

- Rated voltage: 690V AC
- Rated current: up to 125A
- Standard: IEC/EN 60269-2-1, IEC 63211, NFC 63210-63211
- Fuse holder with indicator is available as requested

Item	In(A)	Matched fuse link	Pole No.	Packing(pcs)
STI-32	32A	For 10 X 38 fuse link	1P	12/240
			1P+N/2P	6/120
			3P	4/80
			3P+N	3/60
STI-63	63A	For 14 X 51 fuse link	1P	6/108
			1P+N/2P	3/54
			3P	2/36
			3P+N	1/27
STI-125	125A	For 22 X 58 fuse link	1P	6/108
			1P+N/2P	3/54
			3P	2/36
			3P+N	1/27