



H Type Terminal Block (12 Pole)

- Insert: brass
- Plastic: PE, PP or PA
- Color: Natural, Black
- According to : EN60998-1 EN60998-2-1
- Working temperature: -40°C to +65°C for PE
-30°C to +90°C for PP
-40°C to +110°C for PA

Rated current (A)	Section size (mm ²)	Screw size	PE Material Dimension (mm)					
			L (mm)	W (mm)	H (mm)	E (mm)	e (mm)	Ød (mm)
3	2.5-4.0	M2.5	92.3	16.8	12.3	7.8	5.7	3.0
6	4.0-6.0	M3.0	115.4	18.8	15.4	9.6	6.3	3.3
10	6.0-10.0	M3.0	129.3	20.7	16.5	11.0	7.6	4.2
15	10-12	M3.5	137.8	22.5	18.6	11.7	8.6	4.5
20	12-14	M4.0	138.0	22.5	19.0	12.0	8.6	4.6
30	16	M4.0	164.0	25.5	20.0	13.7	9.3	5.5
60	25	M4.0	186.0	29.2	25.3	15.7	10.8	6.6
80	35	M5.0	226.8	36.1	29.0	19.2	13.2	8.0
100	40	M6.0	254.6	45.0	34.7	20.5	19.2	9.0

Rated current (A)	Section size (mm ²)	Screw size	PP Material Dimension (mm)					
			L (mm)	W (mm)	H (mm)	E (mm)	e (mm)	Ød (mm)
3	2.5-4.0	M2.5	93.9	17.0	12.8	8.0	5.9	3.0
6	4.0-6.0	M3.0	116.6	19.0	15.5	9.9	6.3	3.3
10	6.0-10.0	M3.0	131.5	21.0	16.5	11.5	7.6	4.2
15	10-12	M3.5	139.8	22.8	18.9	12.0	8.6	4.5
20	12-14	M4.0	140.2	22.9	20.3	12.2	9.4	4.6
30	16	M4.0	167.5	25.9	20.2	14.2	9.4	5.5
60	25	M4.0	189.0	29.7	25.8	15.7	11.0	6.6
80	35	M5.0	231.0	36.7	29.6	19.5	13.6	8.0
100	40	M6.0	256.0	45.5	35.6	22.0	20.5	9.0

Rated current (A)	Section size (mm ²)	Screw size	PA Material Dimension (mm)					
			L (mm)	W (mm)	H (mm)	E (mm)	e (mm)	Ød (mm)
3	2.5-4.0	M2.5	95.3	17.5	13.0	8.0	6.0	3.0
6	4.0-6.0	M3.0	117.4	19.0	15.5	10.0	6.3	3.3
10	6.0-10.0	M3.0	132.6	21.2	16.6	11.0	7.6	4.2
15	10-12	M3.5	142.0	23.2	19.0	11.8	8.6	4.5
20	12-14	M4.0	142.5	23.4	20.4	12.2	9.4	4.6
30	16	M4.0	169.0	26.1	20.5	14.2	9.4	5.5
60	25	M4.0	192.0	30.0	26.0	16.2	11.0	6.6
80	35	M5.0	233.5	37.0	29.8	20.0	13.8	8.0
100	40	M6.0	262.0	46.1	35.7	22.5	20.5	9.0