



Products Characteristic

- Function:
 - wire coat and insulation.
 - make the joint of terminal block and wire insulated.
 - divide the colors
 - water-proof
 - application: -40°C~50°C
 - initial shrinkage temperature: 70°C; ultrathin fully shrinkage temperature: 105°C; ordinary fully shrinkage temperature: 125°C
 - protection and insulation of electrical resistance and electrical capacitors
- Standard color: black, red, white, yellow, green, blue and green/yellow

Basic Data

Item	As supplied		After shrinkage		Application
	I.d	thickness	I.d	thickness	
DRS-1	1.2±0.3	0.20±0.05	0.48±0.1	0.32±0.05	0.75~0.9
DRS-2	2.2±0.3	0.25±0.05	0.98±0.1	0.32±0.05	1.1~1.8
DRS-3	3.2±0.4	0.25±0.05	1.45±0.2	0.35±0.05	1.6~2.7
DRS-4	4.2±0.4	0.25±0.05	1.96±0.2	0.35±0.05	2.1~3.6
DRS-5	5.2±0.4	0.25±0.05	2.48±0.2	0.35±0.05	2.6~4.5
DRS-6	6.2±0.4	0.28±0.15	2.96±0.3	0.45±0.15	3.1~5.4
DRS-7	7.2±0.4	0.28±0.15	3.48±0.3	0.45±0.15	3.7~6.3
DRS-8	8.2±0.5	0.28±0.15	3.95±0.3	0.45±0.15	4.2~7.2
DRS-9	9.2±0.5	0.30±0.15	4.40±0.3	0.50±0.15	4.7~8.0
DRS-10	10.2±0.5	0.30±0.15	4.90±0.3	0.50±0.15	5.2~9.0
DRS-11	11.2±0.5	0.30±0.15	5.40±0.3	0.50±0.15	5.7~10
DRS-12	12.2±0.5	0.30±0.15	5.90±0.5	0.50±0.15	6.2~11
DRS-13	13.2±0.5	0.33±0.15	6.40±0.5	0.50±0.15	6.7~12
DRS-14	14.2±0.5	0.35±0.15	6.90±0.5	0.50±0.15	7.3~13
DRS-15	15.2±0.6	0.38±0.15	7.40±0.5	0.60±0.15	7.8~14
DRS-16	16.2±0.6	0.38±0.15	7.90±0.5	0.60±0.15	8.3~15
DRS-18	18.2±0.6	0.40±0.15	8.90±0.5	0.60±0.15	9.3~17
DRS-20	20.2±0.8	0.40±0.20	9.90±0.5	0.70±0.20	11.4~19
DRS-22	22.2±0.8	0.42±0.20	10.80±1.0	0.70±0.20	12.4~21
DRS-25	25.3±0.8	0.45±0.20	12.30±1.0	0.70±0.20	12.8~24
DRS-28	28.3±0.8	0.45±0.20	13.50±1.0	0.70±0.20	14.4~27
DRS-30	30.2±0.8	0.45±0.20	14.70±1.0	0.70±0.20	16~29
DRS-35	35.2±0.8	0.50±0.20	17.30±1.0	0.80±0.20	18~34
DRS-40	40.0±1.0	0.50±0.20	19.80±1.0	0.80±0.20	21~39
DRS-50	50.0±1.0	0.50±0.20	24.80±1.0	0.80±0.20	26~49
DRS-60	60.0±1.0	0.60±0.20	29.80±1.0	0.80±0.20	35~55
DRS-70	70.0±1.0	0.65±0.20	34.00±2.0	1.00±0.20	40~65
DRS-80	80.0±1.0	0.65±0.20	39.00±2.0	1.00±0.20	45~75
DRS-90	90.0±1.0	0.65±0.20	44.00±2.0	1.00±0.20	50~85
DRS-100	100.0±2.0	0.65±0.20	49.00±2.0	1.00±0.20	55~95
DRS-120	120.0±2.0	0.70±0.20	59.00±2.0	1.20±0.20	65~115
DRS-150	150.0±2.0	0.70±0.20	74.00±2.0	1.20±0.20	80~145