

# CFR7-63

## Residual Current Circuit Breaker



### Description

Residual current circuit breaker provides the protection against earth fault/leakage current and isolation function. Also provides the indirect protection against the operator and the protection of the fire caused by the electric circuit faulty.

### Technical Data

- Standard: IEC61008
- Residual current characteristics: A, AC
- Pole No.: 2P, 4P
- Rated making and breaking capacity: 630A
- Rated current(A): 25,40,63
- Rated voltage: 240/415V AC
- Rated frequency: 50/60Hz
- Rated residual operating current  $I_{\Delta n}$ (mA): 30,100,300,500
- Rated residual non operating current  $I_{\Delta no}$ :  $0.5I_{\Delta n}$
- Rated conditional short-circuit current  $I_{nc}$ : 10kA
- Rated conditional residual short-circuit Current  $I_{\Delta c}$ : 10kA
- Tripping duration: instantaneous tripping  $\leq 0.1s$
- Residual tripping current range:  $0.5I_{\Delta n} \sim I_{\Delta n}$
- Electro-mechanical endurance: 4000 cycles
- Connection capacity: Rigid conductor 25mm<sup>2</sup>
- Connection terminal:
  - Screw terminal
  - Pillar terminal with clamp
- Fastening torque: 2.0Nm
- Installation:
  - On symmetrical DIN rail 35mm

B

### Wiring Diagram



### Overall & Installation Dimensions

