



Self-locking Nylon Cable Ties

- Material: Nylon 66, 94V-2 certificated by UL. Heat-resisting, Acid & erosion control, insulate well and not apt to age.
- Operating temperature: -35°C to 85°C
- Color: Natural, UV black and other colors are available as requested

Item No.	Width (mm)	Length (mm)	Max. Bundle Dia. (mm)	Min. Loop Tensile Strength (lbs)	Min. Loop Tensile Strength (kgs)
2.5X100	2.5	100	22	18	8
2.5X120	2.5	120	28	18	8
2.5X150	2.5	150	35	18	8
2.5X160	2.5	160	40	18	8
2.5X200	2.5	200	50	18	8
3.6X100	3.6	100	22	40	18
3.6X150	3.6	150	35	40	18
3.6X200	3.6	200	50	40	18
3.6X250	3.6	250	65	40	18
3.6X300	3.6	300	80	40	18
3.6X350	3.6	350	90	40	18
3.6X370	3.6	370	98	40	18
3.6X400	3.6	400	105	40	18
4.6X120	4.6	120	28	50	22
4.6X150	4.6	150	35	50	22
4.6X200	4.6	200	50	50	22
4.6X250	4.6	250	65	50	22
4.6X280	4.6	280	70	50	22
4.6X300	4.6	300	80	50	22
4.6X350	4.6	350	90	50	22
4.6X380	4.6	380	102	50	22
4.6X400	4.6	400	105	50	22
4.6X450	4.6	450	125	50	22
4.6X500	4.6	500	145	50	22



Self-locking Nylon Cable Ties

Item No.	Width (mm)	Length (mm)	Max. Bundle Dia. (mm)	Min. Loop Tensile Strength (lbs)	Min. Loop Tensile Strength (kgs)
7.2X200	7.2	200	50	120	55
7.2X250	7.2	250	65	120	55
7.2X300	7.2	300	80	120	55
7.2X350	7.2	350	90	120	55
7.2X380	7.2	380	102	120	55
7.2X400	7.2	400	105	120	55
7.2X450	7.2	450	125	120	55
7.2X500	7.2	500	145	120	55
7.2X550	7.2	550	160	120	55
7.2X600	7.2	600	170	120	55
9.0X400	9.0	400	105	175	80
9.0X450	9.0	450	125	175	80
9.0X500	9.0	500	145	175	80
9.0X550	9.0	550	160	175	80
9.0X600	9.0	600	170	175	80
9.0X650	9.0	650	190	175	80
9.0X700	9.0	700	205	175	80
9.0X720	9.0	720	215	175	80
9.0X760	9.0	760	225	175	80
9.0X800	9.0	800	237	175	80
9.0X850	9.0	850	248	175	80
9.0X900	9.0	900	260	175	80
9.0X1000	9.0	1000	275	175	80

J